

Size	Nominal Insulation Thickness	Diameter of insulation (Approx.)	Nominal Thickness outer sheath	Diameter cable (Approx.)	Weight of product (Approx)	Max. DC conductor resistance at 20°C	Min. insulation resistance at 70°C	Current carrying capacity in air		Standard delivery length
								at 30°C	at 40°C	
mm ²	mm	mm	mm	mm	kg/km	Ω/km	MΩ.km	A	A	m
2x0.75	0.6	2.4	0.8	6.4	58	26.0	0.011	6	5.5	50/100/coil
2x1	0.6	2.5	0.8	6.6	64	19.5	0.010	10	9.2	50/100/coil
2x1.5	0.7	3.0	0.8	7.6	88	13.3	0.010	15	13.8	50/100/coil
2x2.5	0.8	3.7	1.0	9.4	137	7.98	0.009	20	18.4	50/100/coil
3x0.75	0.6	2.4	0.8	6.8	69	26.0	0.011	6	5.5	50/100/coil
3x1	0.6	2.5	0.8	6.9	76	19.5	0.010	10	9.2	50/100/coil
3x1.5	0.7	3.0	0.9	8.3	111	13.3	0.010	15	13.8	50/100/coil
3x2.5	0.8	3.7	1.1	10.2	172	7.98	0.009	20	18.4	50/100/coil
4x0.75	0.6	2.4	0.8	7.4	83	26.0	0.011	6	5.5	50/100/coil
4x1	0.6	2.5	0.9	7.8	96	19.5	0.010	10	9.2	50/100/coil
4x1.5	0.7	3.0	1.0	9.2	139	13.3	0.010	15	13.8	50/100/coil
4x2.5	0.8	3.7	1.1	11.1	210	7.98	0.009	20	18.4	50/100/coil