

Size	Nominal Insulation Thickness	Diameter of insulation (Approx.)	Nominal Thickness outer sheath	Diameter cable (Approx.)	Weight of product (Approx)	Max. DC conductor resistance at 20°C	Min. insulation resistance at 70°C	Current carrying capacity in air		Standard delivery length
								at 30°C	at 40°C	
mm ²	mm	mm	mm	mm	kg/km	Ω/km	MΩ.km	A	A	m
2x1.5	0.7	2.8	1.2	8.7	122	12.1	0.010	19	16	50/100/coil
2x2.5	0.8	3.4	1.2	9.9	164	7.41	0.009	25	22	50/100/coil
2x4	0.8	3.8	1.2	10.8	211	4.61	0.0077	34	30	50/100/coil
2x6	0.8	4.3	1.2	11.8	267	3.08	0.0065	44	39	50/100/coil
2x10	1.0	5.5	1.4	15.0	438	1.83	0.0065	61	53	1,000/drum
3x1.5	0.7	2.8	1.2	9.2	142	12.1	0.010	19	16	50/100/coil
3x2.5	0.8	3.4	1.2	10.4	194	7.41	0.009	25	22	50/100/coil
3x4	0.8	3.8	1.2	11.4	254	4.61	0.0077	34	30	50/100/coil
3x6	0.8	4.3	1.4	12.8	339	3.08	0.0065	44	39	50/100/coil
3x10	1.0	5.5	1.4	15.8	538	1.83	0.0065	61	53	1,000/drum
4x1.5	0.7	2.8	1.2	9.9	168	12.1	0.010	19	16	50/100/coil
4x2.5	0.8	3.4	1.2	11.3	233	7.41	0.009	25	22	50/100/coil
4x4	0.8	3.8	1.4	12.8	320	4.61	0.0077	34	30	50/100/coil
4x6	0.8	4.3	1.4	14.4	431	3.08	0.0065	44	39	50/100/coil
4x10	1.0	5.5	1.4	17.2	659	1.83	0.0065	61	53	1,000/drum
5x1.5	0.7	2.8	1.2	10.7	200	12.1	0.010	19	16	50/100/coil
5x2.5	0.8	3.4	1.2	12.3	280	7.41	0.009	25	22	50/100/coil
5x4	0.8	3.8	1.4	14.3	404	4.61	0.0077	34	30	50/100/coil
5x6	0.8	4.3	1.4	15.6	522	3.08	0.0065	44	39	50/100/coil
5x10	1.0	5.5	1.4	18.8	804	1.83	0.0065	61	53	1,000/drum